



## One Tank-Five Chambers-Total Treatment



Sometimes, the simplest solution is the best and that's the case with the EnviroServer. Simple, because the entire treatment system is in one tank. Simple, because the only moving part is the blower. Simple, because there is minimal intrusion to the landscape. Simple, because the process is accomplished with aeration and agitation, the same technology as sewer treatment plants. Simply simple! The CS Series was engineered to treat commercial high strength wastewater in a small economical footprint while providing reliable treatment and superior effluent quality.

### Standard CS Series

CS Model	Max Hydraulic Capacity <sup>1</sup> (Gallons Per Day)	Liquid Capacity (Gallons)	Dimensions (D X L)	Max Organic Load <sup>2</sup>
CS400	400	1,500 GAL	5' X 13' 5"	2.5 LBS
CS550	550	1,900GAL	5' X 17' 1"	3.5 LBS
CS650	650	2,400 GAL	6' X 14' 7"	4.0 LBS
CS750	750	2,800GAL	6' X 17' 1"	4.5 LBS
CS900	900	3,300 GAL	6" x 19' 7"	5.5 LBS
CS1050	1050	3,800 GAL	6' X 22' 3"	6.5 LBS
CS1150	1150	4,500 GAL	8' X 15' 6"	7.0 Lbs
CS1300	1300	4,900 GAL	8' X 16' 9"	8.0 LBS
CS2150	2150	7,500 GAL	8' X 25' 4"	13.5 Lbs

CS Series designed for treating wastewater, commercial high-strength: Non-toxic, non-hazardous wastewater from commercial establishments to domestic strength wastewater <180 mg/l BOD/TSS. <sup>1</sup>Influent wastewater should not exceed constituents of 900 mg/L BOD/TSS with Max FOG Loading of 50 Mg/L and TN of <150 mg/L. <sup>2</sup>Max organic loading is a combined total of BOD, FOG, and TN.